

UC-SILENTIS



Energy-efficient.
Minimal and low-noise.

- **Simple and compact installation with Curved Frontal Design.**
- High Performance plastic Housing design and Helico-Centrifugal Impeller.
- **Very Low Noise Level**
- Fitted with Low Consumption Motor class B and thermal cut out, ambient temperature max. 40°C
- Rated Voltage 220-240V 50/60Hz.
- Timer and Timer-Hygro models available
- IP-44 and Double Insulation
- Basic Back draught Shutter (included)



Coming soon.

CODE	MODEL	COLOR	EAN CODE	VERSION	Ø (mm)	Voltage (V)	SPEED (r.p.m)	Input Power (W)	Maximum Airflow (m³/h)	Sound Pressure Level dB(A)	Weight (Kg)	Units per box	110-127V 60Hz on request
HYGRO SERIES													
01220200	UC-10 SILENTIS HYGRO WHITE		8422248365451		100	230	2300	8	105	26	0,60	6	-
01221200	UC-10 SILENTIS HYGRO SILVER		8422248365475		100	230	2300	8	105	26	0,60	6	-
01222200	UC-10 SILENTIS HYGRO BLACK		8422248365468		100	230	2300	8	105	26	0,60	6	-
TIMER SERIES													
01220100	UC-10 SILENTIS TIMER WHITE		8422248365420		100	230	2300	8	105	26	0,60	6	-
01221100	UC-10 SILENTIS TIMER SILVER		8422248365444		100	230	2300	8	105	26	0,60	6	-
01222100	UC-10 SILENTIS TIMER BLACK		8422248365437		100	230	2300	8	105	26	0,60	6	-
STANDARD SERIES													
01220000	UC-10 SILENTIS STD WHITE		8422248365390		100	230	2300	8	105	26	0,60	6	✓
01221000	UC-10 SILENTIS STD SILVER		8422248365413		100	230	2300	8	105	26	0,60	6	✓
01222000	UC-10 SILENTIS STD BLACK		8422248365406		100	230	2300	8	105	26	0,60	6	✓



STANDARD In combination with light, fans switches on.



TIMER Electronic timer adjustable from 3 to 15 minutes.



HYGRO Adjustable humidity detector from 40% to 95%, and adjustable electronic timer from 0 to 15 minutes.

UC-SILENTIS

